

**WIRE TO BOARD  
HOUSING**

**INTERCOM**



- Features** Single row housing for crimping contact  
Double Wipe Removable contact  
AWG 22 - 24 - 26 - 28
- Material** Insulator: Black glass filled polyester UL 94V0
- Electrical** Current rating: 3 A maxi  
Dielectric withstanding: 500 V AC  
Insulation resistance: 100000 MΩ mini  
Contact resistance: 20 mΩ maxi
- Mechanical** Temperature rating: -55 °C to 125 °C  
Maximum Insulation  
Diameter: Ø 1.45 mm
- Packaging** Recyclable cardboard boxes

**Product Code**

A	B	C	D
485	3248	0xx	740

**C** Number of contacts 02, 03, 04, 05, 08, 10

**WIRE TO BOARD  
HOUSING**

**INTERCOM**



- Features** Double row housing for crimping contact  
Double Wipe Removable contact  
AWG 22 - 24 - 26 - 28
- Material** Insulator: Black glass filled polyester UL 94V0
- Electrical** Current rating: 3 A maxi  
Dielectric withstanding: 500 V AC  
Insulation resistance: 1000 MΩ mini  
Contact resistance: 20 mΩ maxi
- Mechanical** Temperature rating: -40 °C to 125 °C  
Maximum Insulation  
Diameter: Ø 1.45 mm
- Packaging** Recyclable cardboard boxes

**Product Code**

A	B	C	D
485	3401	0xx	740

**C** Number of contacts 08 or 10

