			Г	117.6					
	1/2-28UNEFH17.6					Length		SQ6.5	
									D
	Part Number KM-022602-004 KM-022602-0300 KM-022602-1M	Length (IN) 4±0.15 11.811±3% 39.370±3%	10 30 10	01.6±4 00±3% 00±3%			1/4-36UNS H8 12		С
 Orient SMA plug interface with respect to TNC 'D FLAT' as shown within ± 10°. Connector orientation for cable length less than 150mm only. Additional lengths can be provided by changing XXXX to desired length in MM, or XXX to desired length in INCH. Any queries feel free to consult our sales team at SALES@DGKEMY.COM 					H15.9				В
 3 SMA 2 TNC 1 Coas 	(M) R/A Plug (F) BHD Jack IP67 xial Cable	1 KM-010511 1 RD316	tion	RoHS Compliant	* MAJOR DIMENSION UNLESS OTHERWISE NOTED TOLERANCES	CHECKED TERRY DRAWN KEVIN DRAW	C BHD Jack with O-Ring A R/A Plug, Various Leng	(IP67) - RD316 - uths	A
	4 Hea 3 SMA 2 TNC	KM-022602-004 KM-022602-0300 KM-022602-1M • Orient SMA plug intershown within ± 10°. less than 150mm on • Additional lengths cardesired length in MM • Any queries feel free SALES@DGKEMY. 4 Heat Shrink Tube 3 SMA (M) R/A Plug 2 TNC (F) BHD Jack IP67 1 Coaxial Cable	Part Number Length (IN) KM-022602-004 4±0.15 KM-022602-0300 11.811±3% KM-022602-1M 39.370±3% • Orient SMA plug interface with resp shown within ± 10°. Connector orien less than 150mm only. • Additional lengths can be provided I desired length in MM, or XXX to des • Any queries feel free to consult our SALES@DGKEMY.COM 4 Heat Shrink Tube 2 Black 3 SMA (M) R/A Plug 1 KM-010571 2 TNC (F) BHD Jack IP67 1 KM-010511 1 Coaxial Cable 1 RD316	Part Number Length (IN) Length KM-022602-004 4±0.15 10 KM-022602-0300 11.811±3% 30 KM-022602-1M 39.370±3% 10 • Orient SMA plug interface with respect to TN shown within ± 10°. Connector orientation for less than 150mm only. • Additional lengths can be provided by change desired length in MM, or XXX to desired len • Additional lengths can be provided by change desired length in MM, or XXX to desired len • Any queries feel free to consult our sales teal SALES@DGKEMY.COM 4 Heat Shrink Tube 2 Black 3 SMA (M) R/A Plug 1 KM-011057 2 TNC (F) BHD Jack IP67 1 KM-010511 1 Coaxial Cable 1 RD316	Part Number Length (IN) Length (MM) KM-022602-004 4±0.15 101.6±4 KM-022602-0300 11.811±3% 300±3% KM-022602-1M 39.370±3% 1000±3% • Orient SMA plug interface with respect to TNC 'D FLAT' as shown within ± 10°. Connector orientation for cable length less than 150mm only. • Additional lengths can be provided by changing XXXX to desired length in INCH. • Additional lengths can be provided by changing XXXX to desired length in MM, or XXX to desired length in INCH. • Any queries feel free to consult our sales team at SALES@DGKEMY.COM 4 Heat Shrink Tube 2 Black 3 SMA (M) R/A Plug 1 KM-011057 2 TNC (F) BHD Jack IP67 1 KM-010511 1 Coaxial Cable 1 RD316	Part Number Length (IN) Length (MM) KM-022602-004 4±0.15 101.6±4 KM-022602-0300 11.811±3% 300±3% KM-022602-1M 39.370±3% 1000±3% • Orient SMA plug interface with respect to TNC 'D FLAT' as shown within ± 10°. Connector orientation for cable length less than 150mm only. • Additional lengths can be provided by changing XXXX to desired length in INCH. • Additional lengths can be provided by changing XXXX to desired length in MM, or XXX to desired length in INCH. • Any queries feel free to consult our sales team at SALES@DGKEMY.COM 4 Heat Shrink Tube 2 Black 3 SMA (M) R/A Plug 1 KM-01057 2 TNC (F) BHD Jack IP67 1 KM-010511 Incertain team 1 Coaxial Cable 1 RD316 Incertain team	Part Number Length (IN) Length (MM) KM-022602-004 4±0.15 101.6±4 KM-022602-0300 11.811±3% 300±3% KM-022602-1M 39.370±3% 1000±3% • Orient SMA plug interface with respect to TNC 'D FLAT' as shown within ± 10°. Connector orientation for cable length less than 150mm only. • Additional lengths can be provided by changing XXXX to desired length in INCH. • Additional lengths can be provided by changing XXXX to desired length in INCH. • Any queries feel free to consult our sales team at SALES@DGKEMY.COM 4 <u>Heat Shrink Tube 2 Black 3 SMA (M) R/A Plug 1 KM-011057 2 TNC (F) BHD Jack IP67 1 RD316 Coaxial Cable 1 RD316 RD31</u>	Part Number Length (IN) Length (MM) MACON D22602-004 4±0.15 101.6±4 KM-022602-0300 11.811±3% 300±3% KM-022602-1M 39.370±3% 1000±3% • Orient SMA plug interface with respect to TNC 'D FLAT' as shown within ± 10°. Connector orientation for cable length less than 150mm only. Image: Connector orientation for cable length in INCH. • Any queries feel free to consult our sales team at SALES@DGKEMY.COM SALES@DGKEMY.COM Image: Connector orientation for cable length in INCH. 4 Heat Shrink Tube 2 Black Image: Connector orientation for cable length in INCH. 2 TNC (F) BHD Jack IP67 1 KM-011057 Image: Connector orientation for cable length in INCH. 2 TNC (F) BHD Jack IP67 1 KM-010511 Image: Connector orientation for cable length in INCH. 1 Coaxial Cable 1 RD316 Image: Connector orientation for cable length in INCH. Image: Connector orientation for cable length in INCH. 4 Heat Shrink Tube 2 Black Image: Connector orientation for cable length in INCH. Image: Connector orientation for cable length in INCH. 4 Heat Shrink Tube 2 Black Image: Connector orientation for cable length in INCH.<	Part Number Length (IN) Length (MM) interpretendent interpretendent interpretendent interpreten

5

4

3

All rights reserved. www.dgkemy.com

8

7

6