

PG Type Plastic Waterproof Cable Gland



Material:

Adopting nylon PA66 certificated by UL

Weather strip:

Nitrile butadiene rubber (NBR), Weathering-resistance rubber (EPDM)

Working temperature:


-40℃ to 100℃ in static state, instantaneous heat resistance up to 120℃; -20℃ to 80℃ in dynamic state, instantaneous heat resistance up to 100℃

Characteristics:

IP68(Rotate the part, and use O ring)

Color:

Black(RAL9005), light grey(RAL7035), as well as special colors that can be designed at request.



Type	∅k Cable Range (mm)	Thread O. D. AG (mm)	Thread Length GL (mm)	Spanner Size (mm)
PG7	3~6.5	12.5	8	16
PG7	2~5	12.5	8	16
PG9	4~8	15.2	8	19
PG9	2~6	15.2	8	19
PG11	5~10	18.6	8	22
PG11	3~7	18.6	8	22
PG13.5	6~12	20.4	10	24
PG13.5	5~9	20.4	10	24
PG16	10~14	22.5	10	27
PG16	7~12	22.5	10	27
PG19	12~16	24	10	27
PG19	10~13	24	10	27
PG21	13~18	28.3	10	33
PG21	9~16	28.3	10	33
PG25	16~21	30	11	35
PG25	13~18	30	11	35
PG29	18~25	37	12	42
PG29	13~20	37	12	42
PG36	22~32	47	14	52
PG36	20~26	47	14	52
PG42	32~38	54	14	60
PG42	25~31	54	14	60
PG48	37~44	59.3	15	64
PG48	29~35	59.3	15	64
PG63	42~50	71	28	77
PG63	32~40	71	28	77

M Type Plastic Waterproof Cable Gland



Material:

Adopting nylon PA66 certificated by UL

Weather strip:

Nitrile butadiene rubber (NBR), Weathering-resistance rubber (EPDM)

Working temperature:


-40°C to 100°C in static state, instantaneous heat resistance up to 120°C; -20°C to 80°C in dynamic state, instantaneous heat resistance up to 100°C

Characteristics:

IP68(Rotate the part, and use O ring)

Color:

Black(RAL9005),light grey(RAL7035), as well as special colors that can be designed at request.



Type	ØK Cable Range (mm)	Thread O. D. AG (mm)	Thread Length GL (mm)	Spanner Size (mm)
M12 x 1.5	3~6.5	12	8	16
M12 x 1.5	2~5	12	8	16
M16 x 1.5	4~8	16	8	19
M16 x 1.5	2~6	16	8	19
M18 x 1.5	5~10	18	8	22
M18 x 1.5	3~7	18	8	22
M20 x 1.5	6~12	20	10	24
M20 x 1.5	5~9	20	10	24
M22 x 1.5	10~14	22	10	27
M22 x 1.5	7~12	22	10	27
M24 x 1.5	12~16	24	10	27
M24 x 1.5	10~13	24	10	27
M25 x 1.5	13~18	25	10	33
M25 x 1.5	9~16	25	10	33
M27 x 1.5	13~18	27	10	33
M27 x 1.5	9~16	27	10	33
M30 x 1.5	16~21	30	11	35
M30 x 1.5	13~18	30	11	35
M32 x 1.5	16~21	32	11	35
M32 x 1.5	13~18	32	11	35
M36 x 1.5	18~25	36	12	42
M36 x 1.5	13~20	36	12	42
M40 x 1.5	22~32	40	14	52
M40 x 1.5	20~26	40	14	52
M50 x 1.5	32~38	50	14	60
M50 x 1.5	25~31	50	14	60
M63 x 1.5	37~44	63	15	64
M63 x 1.5	29~35	63	15	64
M71 x 1.5	42~50	71	28	77
M71 x 1.5	32~40	71	28	77