

PG/M Type Plastic Threaded Plug



Material:

Adopting nylon PA66 certificated by UL

Weather strip:


Nitrile butadiene rubber (NBR), Weathering-resistance rubber (EPDM)

Working temperature: -20°C to 80°C

Characteristics: IP68

Color:

Black(RAL9005), light grey(RAL7035), as well as special colors that can be designed at request.



Type	Thread O. D. AG (mm)	Thread Length GL (mm)	Main Body Dimensions H (mm)	Cover Dimensions D (mm)
PG7	12.5	8.5	12.5	15
PG9	15.2	8.5	13	19
PG11	18.6	9	13	22
PG13.5	20.4	9	13	25
PG16	22.5	10.5	15	27
PG21	28.3	10.5	15.5	33
PG29	37	11.5	16	44
PG36	47	13.5	18	55
PG42	54	13.5	18.5	62
PG48	59.3	14.5	19.5	68

Type	Thread O. D. AG (mm)	Thread Length GL (mm)	Main Body Dimensions H (mm)	Cover Dimensions D (mm)
M12 x 1.5	12	8.5	12.5	15
M16 x 1.5	16	8.5	13	19
M18 x 1.5	18	9	13	22
M20 x 1.5	20	9	13	25
M22 x 1.5	22	10.5	15	27
M25 x 1.5	25	10.5	15.5	30
M27 x 1.5	27	10.5	15.5	33
M32 x 1.5	32	10.5	16	38
M40 x 1.5	40	11.5	16	46
M50 x 1.5	50	13.5	18	56
M63 x 1.5	63	14	19	68