



PART NO.	T	SUGGESTED CURRENT
PCR187	0.5 ^{±0.05}	10Amps
PCR187(0.8)	0.8 ^{±0.05}	15Amps

NOTE: 1. THE BEST USE TIME OF TIN PLATING PARTS ARE WITHIN 3 MONTHS SINCE MFG DATE.
 鍍錫最佳使用時間，為製造日起3個月內。
 2. FINISH: TIN PLATED. IF PARTS ARE NOT USED UP PLEASE STORE IN A SEAL BAG.
 表面為鍍錫，未使用完畢時，產品請密封。



K 康揚企業股份有限公司
 KANG YANG HARDWARE ENTERPRISE CO., LTD.
 康揚塑膠(東莞)有限公司
 KANG YANG PLASTIC(DONG GUAN)CO.,LTD.
 康哲電腦配件(吳江)有限公司
 KANG CHE COMPUTER COMPONENTS(WUJIANG)CO.,LTD.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF KANG YANG HARDWARE ENTERPRISE CO. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF KANG YANG HARDWARE ENTERPRISE CO. IS PROHIBITED. DO NOT SCALE DRAWING	DATE	2003.01.14	TITLE	P.C.B TERMINAL	DWG. NO.	PART NO.	
	DRAWN	JASON	MATERIAL	BRASS	PCR187	SEE ABOVE	
	CHECKED		COLOR		SIZE	SPEC. DWG.	REV
	APPROVED		FINISH	TIN PLATED	A4		B
			UNLESS OTHERWISE SPECIFIED TOLERANCE:	SEE ABOVE	SCALE: 5:1	UNIT	SHEET 1 OF 1
						mm	