



PRODUCT DATA SHEET



REFERENCE: 23056

DATE: 27/04/2015

REV: 0

PAGE N° 1/2

DESCRIPTION: CA14FV15-100KA2020 LV10 PCF RT-RO

Customer Approval : Date: _____ Name: _____ Signature: _____

ELECTRICAL PARAMETERS AT 23°C ±5°C AND 40% TO 70% HR:

Nominal Resistance	100K
Resistance Law	Linear With Cut Track at Final
Maximum Power at 50°C	0,22W
Resistance Tolerance	±20%
Temperature Coefficient	500 ppm/°C
Temperature Range	-25°C to +70°C
Electrical Angle	235°±20°

MECHANICAL PARAMETERS:

Max. Push And Pull On The rotor	50N
Dimensional Part's	See drawing PLANO N°02-0738
Wiper Torque	<2,5Ncm
Angle Of Rotation	265°±5°
Max. Torque At End Stop	10Ncm
Wiper Position on Delivery	50% ±15°
Operational Life	10.000 Cycles

TEST:

Thermal Cycling ±2,5%

Initial measure of the resistance value at standard conditions. Put the potentiometers 16h at T^a 85°C follow that 2h at T^a -25C. Measuring of the value variation after 24 in standard conditions. Typical variation of value (95% confidence)



PRODUCT DATA SHEET



REFERENCE: 23056

DATE: 27/04/2015

REV: 0

PAGE N° 2/2

DESCRIPTION: CA14FV15-100KA2020 LV10 PCF RT-RO

Load Life

+0%, -5%

Environmental conditions: T^a 50°C. Voltage applied: The maximum admissible for each value related to the maximum power (See our brochure to check the maximum power for each type of potentiometers). Measures: : Initial measure of the resistance value at standard conditions. Measuring the resistance value at 100h, 250h, 500h and 1.000h to check the advance. The potentiometers are stabilised at 23°C, 50% Hr during 24 hours, and, afterwards they resistance is measured for every time. Typical variation of value (95% confidence)

Mechanical (cycles)

±6%

Environmental conditions 23°C. Cycles: 10.000. Speed: 10 rpm. Typical variation of value (95% confidence)

Soldering Effect

±1%

Initial measure of the resistance value at standard conditions. Immerse the potentiometers at 350° ±10C during 2 sg. The potentiometers are stabilised at 23°C, 50% Hr during 24 hours, and, afterwards they resistance is measured Typical variation of value (95% confidence)

Storage (3 years)

±3%

Initial measure of the resistance value at standard conditions. Store the potentiometers during 3 years at 23°C, 50% Hr. Measuring of the total variation of value at 1st year, 2nd year and 3rd year. Typical variation of value after 3 years (95% confidence)

Damp Heat

+5%, -2%

Environmental conditions: T^a 40°C, Hr 95%. Measures: Initial measure of the resistance value at standard conditions. Measuring the resistance value at 100h, 250h, and 500h to check the advance. The potentiometers are stabilised at 23°C , 50% Hr during 24 hours, and, afterwards they resistance is measured for every time. Typical variation of value (95% confidence)







ANNEXED

Drawing Code

PLANO N°02-0738

Modifications to customer's specific requirements will be discussed and agreed with the customer. General specifications that are also shown on the catalogue -and which are not customer specific- will be updated on www.acptechnologies.com General specifications are for reference only and are subject to change without notice.

The information contained in this document is confidential. It cannot be copied, disclosed or relayed partially or in full in any format, to third parties without the written consent of ACP.



					Fecha	Nombre	 ARAGONESA DE COMPONENTES PASIVOS S.A.	Referencia Artículo
				Creado	10/06/2010	CEM		
				Revisado				Revisión
				TOLERANCIA GENERAL Angular / Lineal ±1°		ESCALA	CA14FV15 RT-RO	Nº Plano
				$\begin{matrix} < 1 & \pm 0,1 \\ 1..10 & \pm 0,3 \\ > 10 & \pm 0,5 \end{matrix}$				02-0738
Estado	Cambios	Fecha	Nombre	REF. DOCUMENTO :				