

MSDS Report

Prepared For :	SHENZHEN MOTOMA POWER CO., LTD No.321, 3/F, Building A, 5th. Zone, Honghualing Indstrial Zone, Taoyuan Road, Nanshan, ShenZhen, China.
Product Name:	Sealed Lead Acid Battery
Model :	4V,6V,12V ; 0.5AH-250AH
Prepared By:	Shenzhen NCT Testing Technology Co., Ltd. 1 / F, No. B Building, Mianshang Younger Pioneer Park, Han gcheng Road, Gushu Xixiang Street, Baoan District, Shenzhen, Guangdong, China
Report No.:	NCT18051617M1-1

Written by:

Dy lan chen

Hely Wang

Date:

Fax: 86-755-27790922



Report No.: NCT18051617M1-1

Hotline: 400-886-8419

TRF: MSDS-V2

Page 1 of 10 http://www.nct-testing.cn





Material Safety Data Sheet

Section 1- Chemical Product & Company Identification

Product Name: Sealed Lead Acid Battery

Manufacture: SHENZHEN MOTOMA POWER CO., LTD

Address: No.321, 3/F, Building A, 5th. Zone, Honghualing Indstrial Zone, Taoyuan Road,

Nanshan, ShenZhen, China.

Contact Person 联系人: Ms. Wang

Tel 电话: +86-755-83736206

Fax 传真: +86-755-82949256

Emergency Tel 应急电话: +86-755-83736206

E-mail 邮箱: info@motoma.com

Item Code: NCT18051617M1-1

Section 2- Hazards Identification

GHS hazard class		
Health hazard(s)	Skin corrosion/irritation	category1
	Reproductive toxicity	category1
	Specific target organ toxicity, repeated exposure	category2
Environmental	Hazardous to the aquatic environment, long-term	category1
hazard(s)	hazard	
Pictogram	- Annual Control Control	







Report No.: NCT18051617M1-1

Hotline: 400-886-8419

TRF: MSDS-V2

Fax: 86-755-27790922

http://www.nct-testing.cn

g Technology

Effective Date: 2025-01-01

Page 2 of 10



Material Safety Data Sheet

<u>y</u>	
Signal	Danger
Hazard	H314 Causes severe skin burns and eye damage
statement(s)	H360 May damage fertility or the unborn child
	H373 May cause damage to organs through prolonged or repeated
	exposure
	H410 Very toxic to aquatic life with long lasting effects
Precautionary st	atements
Prevention	P260 Do not breathe dust/fume/gas/mist/vapours/spray.
	P264 Wash thoroughly after handling.
	P273 Avoid release to the environment.
	P280 Wear protective gloves/protective clothing/eye protection/face
	protection.
Response	P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce
	vomiting.
	P303+P361+P353 IF ON SKIN (or hair): Take off immediately all
	contaminated clothing. Rinse skin with water [or shower].
	P304+P340 IF INHALED: Remove person to fresh air and keep
	comfortable for breathing.
	P305+P351+P338 IF IN EYES: Rinse cautiously with water for
	several minutes.
	Remove contact lenses, if present and easy to do. Continue rinsing.
	P308+P313 IF exposed or concerned: Get medical advice/ attention.
	P314 Get medical advice/attention if you feel unwell.
	P363 Wash contaminated clothing before reuse.
	P391 Collect spillage.
Storage	P405 Store locked up.
Disposal	P501 Dispose of contents/container in accordance with
	local/regional/national/international regulations

Report No.: NCT18051617M1-1

Hotline: 400-886-8419

TRF: MSDS-V2

Fax: 86-755-27790922

Page 3 of 10

http://www.nct-testing.cn



Section 3- Composition/Information on Ingredients

Hazardous Ingredients (Chemical Name)	Concentration or concentration ranges (%)	CAS Number
Lead Dioxide	1309-60-0	32~35
Lead	7439-92-1	31.1~32.2
Dilute Sulfuric acid	7664-93-9	20~22
ABS plastic	9003-56-9	13~15
Glass Fiber	60676-86-0	2~3
Epoxy resin	N/A sting T	1.5~2.0
other	N/A	0.4~0.6

Labeling according to EC directives.

No symbol and risk phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4- First Aid Measures

After skin contact	Take off the contaminated clothing and shoes immediately.
	Wash off with soap and plenty of water. Consult a physician.
After eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
After ingestion	Do Not induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.
After inhalation	If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

Report No.: NCT18051617M1-1

Hotline: 400-886-8419

TRF: MSDS-V2

Page 4 of 10 Fax: 86-755-27790922

http://www.nct-testing.cn



Section 5- Fire Fighting Measures

Hazardous products of combustion	Lead oxides, sulphur oxides.
Extinguishing method	Use Dry Chemical powder, foam or Carbon dioxide for extinction.
Special protective equipment	Wear self contained breathing apparatus for fire fighting if necessary.

Section 6- Accidental Release Measures

Personal protective measures	Wear acid-resistant clothing, boots, gloves, and face shield.
Environmental protective measures	Prevent the spills inflow to a sewer and then place in suitable container.
Methods for taking in and cleaning up	Contain/absorb small spills with dry sand, earth, and vermiculite. Do not use combustible materials. If possible, carefully neutralize spilled electrolyte with soda ash, sodium bicarbonate, lime, etc.

Section 7-Handling and Storage

Handling	Use personal protective equipment. Ensure adequate
	ventilation. Keep away from sources of ignition – No smoking.
	Avoid contacting with skin and eye.
Storage	Store in a cool (10~40°C), dry area away from combustible
	materials. Do not store in sealed, unventilated areas. Avoid
	overheating and overcharging.

Fax: 86-755-27790922

Report No.: NCT18051617M1-1

Hotline: 400-886-8419

TRF: MSDS-V2

Page 5 of 10

http://www.nct-testing.cn



Section 8 - Exposure Controls/Personal Protection

Engineering Controls	Safety shower and eye bath. Mechanical exhaust required.
Respiratory protection	Use a full-face supplied air respirator.
Eye protection	Wear chemical goggles.
Hand Protection	Wear impervious chemical resistant gloves.
Body protection	Protective work clothing.

Section 9-Physical and Chemical Properties

Appearance and	Outside: Black plastic cement shell
properties	Inside: Sulfuric acid, colorless liquid.
Odor	Odorless
Odor threshold	No data available
PH value	No data available
Melting point/freezing point	No data available
Boiling Point, initial	
boiling point and	No data available
Boiling range	
Flash Point	No data available
Evaporation Rate	No data available
Flammability	No data available
Upper explosive limit	No data available
Lower explosive limit	No data available
Vapor Pressure	No data available
Vapor Density	No data available
Density/relative	No data available

Report No.: NCT18051617M1-1

Hotline: 400-886-8419

TRF: MSDS-V2

Page 6 of 10 Fax: 86-755-27790922

http://www.nct-testing.cn



Material Safety Data Sheet

density	
Solubility in Water	No data available
Octanol/water partition coefficient	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Viscosity	No data available

Section 10 – Stability and Reactivity

Reactivity	No data available
Chemical stability	Stable under the condition recommended.
Possibility of hazardous reaction	No data available
Conditions to avoid	Sparks and other sources of ignition. Prolonged overcharge. Fire or explosion hazard due to possible hydrogen gas generation.
Incompatible materials	Bases, Halides, Organic materials, Carbides, fulminates, Nitrates, picrates, Cyanides, Chlorates, alkali halides, Zinc salts, permanganates, Hydrogen peroxide, Azides, Perchlorates, Nitromethane, phosphorous, cyclopentadiene, cyclopentanone oxime, nitroaryl amines, hexalithium disilicide, phosphorous(III) oxide, Powdered metals.
Hazardous decomposition products	No data available

Report No.: NCT18051617M1-1

Hotline: 400-886-8419

TRF: MSDS-V2

Page 7 of 10 http://www.nct-testing.cn Fax: 86-755-27790922



Section 11 - Toxicological Information

Acute toxicity	Sulfuric Acid: LD50(rat, Oral) 2140mg/kg; LC50(rat, Inhalation,				
Acute toxicity	\$ 10 to 50 ATS1 \$ 10 10 ATS1 \$ 10 AT				
HAMANI CODY TO	2h) 0.51 mg/L				
Skin	No data available				
corrosion/irritation	110 data available				
Serious eye					
damage/eye	No data available				
irritation					
Respiratory or skin sensitization	No data available				
Germ cell	eting To				
mutagenicity	No data available				
Carcinogenicity	Lead (CAS No. 7439-92-1): Group 2B Possibly carcinogenic				
	to humans ;				
	Sulfuric acid (CAS No. 7664-93-9): Group 1 Carcinogenic to				
9	humans (IARC);				
115	Lead dioxide (CAS No. 1309-60-0): No data available;				
Reproductive	No data available				
toxicity					
Specific target	No data available				
organ toxicity –	5008				
single exposure					
Specific target	No data available				
organ toxicity –					
repeated exposure					
Aspiration hazard	No data available				

Section 12-Ecological Information

Toxicity	No data available	
Persistence and	No data available	
Degradability		

Report No.: NCT18051617M1-1


Hotline: 400-886-8419

TRF: MSDS-V2

Fax: 86-755-27790922

Page 8 of 10

http://www.nct-testing.cn





Bioaccumulative potential	No data available
Mobility in soil	No data available
Other adverse effects	Very toxic to aquatic life with long lasting effects.

Section 13 - Disposal Considerations

Property of waste:	Neutralized acid may be flushed down the sewer. Spent patteries must be treated as hazardous waste and disposed of according to local state, and federal regulations. A copy of this material safety date must be supplied to any scrap dealer or secondary smelter with battery.	
Methods of disposal:	Dispose of in a manner consistent with federal, state, and local regulations.	
Precautions of disposal:	No data available.	

Section 14 - Transport Information

AIR TRANSPORT-ICAO/ATA(2025-2026 Edition of the ICAO Technical instruction for the Safe Transport of Dangerous Goods by Air (Technical Instructions) and the 66th Edition of the IATA Dangerous Goods Regulations (IATA DGR)):

This valve regulated lead-acid battery is exempt from DG regulation and classified as "non-spillable battery", so this battery is not subject to DG regulations, since it meets the requirement of packing instructions 872 of special provision A67.

MARINE TRANSPORT-IMDG Code, 2024 Edition(Amendment 42-24):

This valve regulated lead-acid battery is non-spillable battery and meet the requirements of special provision 238, so it is not subject to the provision of IMDG code.

Section 15 - Regulatory Information

Component	CHINA	TSCA	ENCS	EINECS
Lead	V	V	√	√
Sulfuric acid	V	√	√	√
Lead dioxide	= 3	-	√	√

Report No.: NCT18051617M1-1

Hotline: 400-886-8419

TRF: MSDS-V2

Page 9 of 10 Fax: 86-755-27790922

http://www.nct-testing.cn





Note 1:

CHINA - China Inventory of Existing Chemical Substances (IECSC)

TSCA - United States Inventory of Toxic Substances Control Act Chemical Substances (TSCA)

ENCS - Japan Existing and New Chemical Substances (ENCS)

EINECS - European Inventory of Existing Commercial Chemical Substances (EINECS)

Note 2:

"v" Indicates that the substance included in the regulations

"-" That no data or included in the regulations

Section 16 - Additional Information

The information above is believed to be accurate and represents the best information currently available to us. However, concorde makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.

******End of report*****

Fax: 86-755-27790922

Report No.: NCT18051617M1-1

Hotline: 400-886-8419

TRF: MSDS-V2

Page 10 of 10

http://www.nct-testing.cn