

# Product data sheet

Specifications



## Mini enclosure for modular device, Mureva Enclosure, 1x3 modules, without terminal block

13975

### Main

Range	Mureva
product name	Mureva Enclosure
Product or component type	Weatherproof enclosure
Enclosure type	Mini enclosure for modular device
Mounting plate description	Slotted

### Complementary

Enclosure mounting	Surface
9 mm pitches	6
Number of 18 mm modules per row	3
Total number of 18 mm modules	3
Number of horizontal rows	1
Electrical insulation class	Double insulation Class II
Provided equipment	1 marking kit
Type of front cover	Transparent
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	1
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	80 mm
Height	150 mm
Depth	98 mm
Internal depth	56 mm
Colour	Door: transparent green Enclosure: light grey (RAL 7035)

### Environment

Standards	IEC 61439-3 IEC 60670 IEC 60695-2-1 EN 50262
Fire resistance	650 °C conforming to IEC 60695-2-1

<b>IP degree of protection</b>	IP65 conforming to IEC 60529
<b>IK degree of protection</b>	IK09 conforming to EN 50102
<b>Environmental characteristics (UV)</b>	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
<b>Overvoltage category</b>	II
<b>Ambient air temperature for operation</b>	-25...60 °C

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8.000 cm
<b>Package 1 Width</b>	15.000 cm
<b>Package 1 Length</b>	10.000 cm
<b>Package 1 Weight</b>	266.000 g
<b>Unit Type of Package 2</b>	BB1
<b>Number of Units in Package 2</b>	20
<b>Package 2 Height</b>	22.500 cm
<b>Package 2 Width</b>	34.500 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	5.692 kg
<b>Unit Type of Package 3</b>	P12
<b>Number of Units in Package 3</b>	480
<b>Package 3 Height</b>	80.000 cm
<b>Package 3 Width</b>	80.000 cm
<b>Package 3 Length</b>	120.000 cm
<b>Package 3 Weight</b>	148.610 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Carbon footprint (kg.eq.CO2 per CR, Total Life cycle) 2

Environmental Disclosure [Product Environmental Profile](#)

## Use Better

### Materials and Substances

Minimum percentage of recycled plastic content 24

Packaging made with recycled cardboard No

Packaging without single use plastic No

SCIP Number 5036b720-908f-495f-9f9e-e215274e05b0

China RoHS Regulation [China RoHS declaration](#)

## Use Again

### Repack and remanufacture

Circularity Profile No need of specific recycling operations

Halogen content performance Halogen free product

Take-back No