




SPECIFICATION FOR APPROVAL

COMMODITY	SMD POWER COIL		SPEC NO.	SP-N241118025
ITEM	JNR 4030H-100M	Green	版本：A	表單編號：QR-012-02

(1) DIMENSION: (UNIT: mm)



	DIM.	TOL.
A	4.00	±0.20
B	4.00	±0.20
C	2.80	±0.20
D	1.35	±0.30
E	3.40	±0.40

(2) ELECTRICAL CHARACTERISTIC

TEST INSTRUMENTS.

INDUCTANCE	10 ± 20%	μ H	☐ AGILENT 4294A Precision Impedance Analyzer
TEST FREQUENCY	100	KHz	☐ Agilent 4287A RF LCR Meter
TEST VOLT	1	V	☐ AGILENT 4285A Precision L.C.R.
RDC	100 ± 20%	mΩ	☐ HP-4286A RF L.C.R. Meter.
Isat	2.00 (typ) 1.70 (max)	A	☒ CHROMA 3302 Automatic Components Analyzer.
Irms	1.50 (typ) 1.30 (max)	A	☐ WAYNE KERR 6420 Precision Impedance Analyzer.
			☒ ZENTECH 1320 BIAS CURRENT.
			☒ BK PRECISION 2840 DC Resistance Meter
			☐ ZENTECH 502AC Resistance Merter
			☐ ADEX AX-1155B DC Low Ohm Meter
			☐ WAYNE KERR HI-POT TESTER 7600

REMARK :

1. All test data referenced to 25°C ambient.
2. Saturation Current (Isat) will cause L0 to drop approximately 30%.
3. Heat Rated Current (Irms) will cause the coil temperature rise approximately Δt of 40°C.


PURCHASER CONFIRMED :

APPROVED	CHECKED	DRAWN

TEST REPORT

SPEC NO : SP-N241118025

Typical Performance Curves



Test Instrument :

ZENTECH 3302 Automatic Components Analyzer

ZENTECH 1320 BIAS CURRENT

Testing Condition :

Temperature : 25 to 28°C

Humidity : 60 to 70 % RH

Check by :



Test by :



TEL : 886-2-2689-4971 FAX : 886-2-2689-4260
E-mail : jantek@jantek-elec.com.tw
Web-Site : www.jantek-elec.com.tw